

SPECIFICATIONS

COLLECTION NAME	: Urban Bridge SQ
YARN	: 100% PP
CONSTRUCTION	: Tufted Level Loop
DYE METHOD	: Solution Dyed
GAUGE	: 1/12"
STITCHES PER INCH	: 10
PILE HEIGHT	: 4 mm(+/- 0.5mm)
TOTAL HEIGHT	: 6.5 mm(+/- 0.5mm)
PILE WEIGHT	: 20 oz/sy (680 gm/sm)
TOTAL WEIGHT	: 142 oz/sy (4800gm/sm +/- 200gm/sm)
PRIMARY BACKING	: Non-woven
SECONDARY BACKING	: PVC with fiberglass
SIZE	: 50 x 50 cm/tile
PACKING	: 20 pcs (5 sm)/box




*As with all dyed products, colours are subject to dye lot variations.


PERFORMANCE SPECIFICATIONS

COLOURFASTNESS	: Grade ≥ 4 (AATCC Test Method) : Result: 6 = OK
FLAMMABILITY	: Passed (ASTM E648, GB 8624-2006)
SMOKE DENSITY	: Passed (ASTM E662, GB/T 8627-1999)
STATIC PROPENSITY	: ≤ 3.0 kV (AATCC-134, GB/T 18044-2000)


RECOMMENDED INSTALLATION METHODS :




1/4 Turn



Monolithic



Brick



Ashlar